



Ribbon fibre splicer


# TYPE-72M12



Useful cloud hosted  
splicer services via  
your smartphone App.




**Industry only dual independent ovens and  
Auto Clamping Adjustment System "Active-ACAS"**



Dual independent ovens  
for productivity



Reduce your work time  
Splicing 11s  
Heating 35s



Active ACAS  
optimises splice loss  
0.05dB



Touch optimised  
user interface and  
high resolution display

## Specifications

Items		TYPE-72M12
Optical fibre requirements	Material	Silica glass
	Profile types	Single/ SMF(G652), MMF(G651), DSF(G653), NZDSF(G655), BIF(G657)
	Fibre count	1, 2, 4, 5, 6, 8, 10, 12
	Cladding diameter	125µm
	Coating diameter	Single fibre coating dia: 200µm, 250µm, 500µm, 900µm Ribbon fibre thickness: 200-400µm
	Applicable cable	Drop cable(2.0mm×3.1, or 2.6mm), Indoor cable(2.0mm×1.6mm)
	Cleave length	10mm
Standard performance	Splice loss (typical) *1	SMF 0.05dB, MMF 0.02dB, DSF 0.08dB, NZDSF 0.08dB
	Splice time (typical)	11sec (SM 12c Quick Mode), 14 sec (SM 12c Std. Mode)
	Heating time (typical)	35sec (FPS-6 sleeves, 40mm 1-12c Quick Mode)
	Splice & heat cycles per battery full charge *2	Approx 180
	Fibre view and magnification	2 CMOS cameras observation, 23X (zoom 46X)
	Proof test	1.96-2.09 N
	Applicable protection sleeve	60mm, 40mm & Sumitomo Electric nano sleeves
Programs	Splice programs	Max 300
	Heating programs	Max 100
Functions	Splice image capture / Splice data storage	200 images / 10,000 splice data (internal memory only) 50,200 images / 20,000 splice data (with 16GB SD card)
	Automatic fibre count detection	Provided
	Automatic arc calibration	Automatically compensates for environmental condition changes
	Auto clamping adjustment system	Provided
	Reversible fibre holder system	Provided
	Dual automatic independent heaters	Provided
	User-selectable heater clamp operation	Provided
	Display of remaining Splice & Heat cycles	Provided (Battery mode)
	Onboard user training video	Provided
	Wireless LAN connectivity (Option) *3	Provided
Size / Weight	Size	128 (W) x 154 (D) x 130 (H) mm (without anti-shock rubber)
	Weight	1.8kg(without Battery) / 2.1kg(with Battery BU-16)
	Monitor	5.0" touch screen color LCD display
Terminals	DC output	DC 12V (for JR-6+)
	USB port	USB2.0 (mini-B type)
	Storage media	SD/SDHC memory card MAX32GB
Power supply	AC input	AC 100-240V, 50/60Hz (ADC-16)
	DC input	DC 10-15V, 7.5A
	Battery pack	Li-ion 10.8V, 6400mAh (BU-16)
Operating condition		Altitude : 0-3,660m, Temperature : -10-50°C, Humidity : 0-95%(non-condensing), Wind velocity : up to 15m/sec
Storage condition		Temperature : -40-80°C, Humidity : 0-95%, Battery : -20-30°C(long term)
Electrode life *4		1,500 arc discharges
Software updates		Internet
Data management		Can be stored, edited and analyzed by dedicated PC software

\*1 : Average value of the final inspection in room temperature with Sumitomo Electric identical fibre. Measured by cut-back method relevant to ITU-T and IEC standards.

\*2 : Splice & Heat cycles may vary depending on the battery status and the operating environment.

\*3 : Wireless LAN connectivity is not available in all countries. For more details, please refer to our Web site. <http://global-sei.com/sumitomo-electric-splicers/>

\*4 : Achieved in lab condition. Electrode life may vary depending on the operating environment.

## Environmental Durability\*

	Test details
Shock resistance	Drop from 76cm on 5 faces (excluding top face)
Impact resistance	Equivalent to IK07 on LCD monitor
Water resistance	Equivalent to IPx2
Dust resistance	Equivalent to IP5x

\*Splicer operation after shock, impact, water or dust tests, was confirmed under battery power, by Sumitomo Electric.

Does not guarantee the product will not be damaged by these conditions.

## Basic Accessories

Part name	Part No.	Qty.
AC adapter	ADC-16 series	1 pc
AC power cord	PC-AC<X>*	1 pc
Cooling tray	—	1 pc
Spare electrode	ER-10	1 pair
Operating CD manual	—	1 pc
Quick reference guide	—	1 pc
Carrying case with worktable	CC-72	1 pc
Hand strap	—	1 pc
USB cable	—	1 pc

\*X=2(USA), 3(EU), 4(JP), 5(UK), 6(AUS), 7(South Africa)

Items listed in Basic Accessories are always included with the splicer body. Overall kit content may vary regionally. Please check with your local authorised reseller to confirm kit content in your region.

## Accessories

Part name	Part No.	Remarks
Accessories for Splicer	SumiCloud card	WLS-D series
	FHS-025	For SumiCloud™ connection
	FHS-09	For 0.25 mm single fibre
	FHD-1	For 0.9 mm single fibre
	FHC-3	For drop and indoor cables (single fibre)
	FHM-2	For 3 mm cable
	FHM-4	For 2-fibre ribbon
	FHM-5	For 4-fibre ribbon
	FHM-6	For 5-fibre ribbon
	FHM-8	For 6-fibre ribbon
	FHM-10	For 8-fibre ribbon
	FHM-12	For 10-fibre ribbon
	FHM-12	For 12-fibre ribbon
	PCH-12	200µm to 250µm pitch changing holder for pliable fibre ribbon
	Lynx2-UML-S	For φ3 mm cord and φ0.9 mm single fibre
Accessories	Battery pack	BU-16
	Battery charger	BC-16
	Car battery cable	PCV-16
	Electrodes	ER-10
	V-groove cleaning jig	VG-2
	Handheld fibre cleaver	FC-8R-FC
	Handheld fibre cleaver	FC-8R-F
	Fibre cleaver	FC-6M-C
	Fibre cleaver	FC-6RM-C
	Jacket remover	JR-M03
	Jacket remover	JR-6+
	Fibre protection sleeve	FPS-1
	Fibre protection sleeve	FPS-40
	Fibre protection sleeve	FPS-5
	Fibre protection sleeve	FPS-6
	Alcohol dispenser	HR-3



Carrying case with worktable  
CC-72



Handy cleaver  
FC-8R series



Table-top cleaver  
FC-6 / FC-6R series



Hot jacket remover  
JR-6+



Pitch changing holder  
PCH-12



Available for  
Lynx-Custom Fit™  
Splice-On Connector

Sumitomo Electric Industries, Ltd.