



Data Sheet

RadiSense® 40

Electric Field Probe

Models - RSS2040S | RSS2040H

Accurate

High Speed

Robust



raditeq.com

Publish date: 22/03/2021



RadiSense® 40

Models - RSS2040S - RSS2040H

The high frequency E-field probe

Accurate

High Speed

Robust

Raditeq, the inventor of the first laser powered E-field probe in the world provides a full range of accurate and fast laser powered probes from 9 kHz to 40 GHz. With their long experience and extensive knowledge on laser power technology and field probe measurement technology, the RadiSense® probes provide the most reliable, high quality range of laser powered E-field probes in the market, with unprecedented measurement uncertainty.

Wide range - The RadiSense® 40 has a wide frequency range from 10 MHz to 40 GHz allowing accurate isotropic E field strength measurements within a range from 0.5 V/m to 1000 V/m. This wide range makes the RadiSense® 40 ideal for EMC Automotive, Military/Aerospace and CE marking applications.

Two versions - The RadiSense® 40 is available in two versions: The RSS2040S version provides the most accurate frequency response and isotropy, with a maximum measurement speed of 100 measurements/second (individual X-Y-Z axis + isotropic value). The model RSS2040H has an increased measurement speed of 1000 measurements/second at the cost of a slightly higher uncertainty, intended for applications where speed is more important, like mode stir / reverberation chambers.

Modular - The RadiSense® 40 is intended to be used in combination with the RadiCentre modular test system, which is available as a 1-slot (RadiCentre Slim), 2-slot (RadiCentre) or 7-slot (RadiCentre Pro). The probe is connected to the laser power plug-in card (model LPS2001B) with FC/ST dual fiber links. The plug-in card provides the laser power source and bi-directional communication to the probe. The fiber optic extension cable between the RadiSense® 40 probe and the LPS2001B plug-in card is standard available at three different lengths (10, 20 or 30 m). Other lengths to a maximum of 100 m are available on request.

Internal calibration data - The linearity adjustment data, by default is stored inside the probe. In addition, the frequency response calibration data of the X-Y-Z axis can be stored as user correction data inside the probe. As a result, there is no need to apply frequency dependent corrections for individual axis' in software anymore. This feature results in a high accuracy and ease-of-use.

Software support - The RadiSense® probes are supported by RadiMation and RadiMation Pro, automated EMC test and measurement software packages. The RadiSense® probes can also be controlled with most other brands of commercial EMC test software packages, like ETS Lindgren TILE and R&S EMC32/Elektra.

RadiSense® 40 Specifications

Model	RSS2040S		RSS2040H	
Field measurement range	0.5 to 1000 V/m			
Max input level before damage	2000 V/m			
Frequency range	10 MHz to 40 GHz			
Resolution	0.001 V/m < 0 - 10 V/m 0.01 V/m < 10 - 100 V/m 0.1 V/m > 100 - 1000 V/m			
Accuracy				
Frequency response	± 1 dB		-2 dB to + 5 dB	
Isotropy	± 0.5 dB @ 1 GHz			
Measurement speed (x, y, z and E-Tot)	100 measurements/s		1000 measurements/s	
Linearity	± 0.5 dB ± 0.5 V/m			
Dimensions				
Shape of housing	stalk probe			
Electrical measuring volume	1 cm³			
Total lenght including body	30 cm (11.81 in)			
Number of antennas	3 dipoles			
Environmental conditions				
Temperature range (operating)	0 °C to 40 °C (32 °F to 104 °F)			
Relative humidity (operating)	10 % to 90 % RH (non-condensing)			
Calibration & Power consumption				
Factory adjustment data	Internally stored, ISO17025 calibration (RSS2040S only)			
Accredited calibration (2)	Traceable, accredited calibration with certificate (optional)			
Optical LASER power	Max. 0.5 Watt at aperture @ 808 nm			
Fibre connection & Cable				
Laser fibre optic connector - cable	FC/PC - 200/230 µm fibre			
Data fibre optic connector - cable	ST/PC - 200/230 µm fibre			
Extension fibre length (3)	Standard lengths 10m, 20m or 30m. Maximum 100m			
Safety				
Interlock	External interlock & closed loop safety system			
Warranty (4)	Three years			

¹⁾ Isotropy is the maximum deviation from the geometric mean as defined by IEEE 1309-2013

²⁾ This calibration can be stored inside the probe as user correction data

³⁾ The probe is (as a standard) delivered with a 10 m extension fibre. Other fibre length to maximum 100 m available on request

⁴⁾ Standard warranty is 1 year. After you register your new Raditeq product two (2) years of warranty will be added for free.

Registration can be done at: www.raditeq.com



Raditeq B.V. | Vijzelmolenlaan 3 | 3447GX Woerden | The Netherlands

www.raditeq.com | T: +31 348 200 100